

MULLARD DIRECTLY-HEATED OUTPUT VALVES FOR A.C. SETS—continued

Type.	Description.	Base.	Bulb Finish.	If.	Characteristics at $V_a = 100$; $V_g = 0$.			(a) V_a	(b) V_s or V_{aux}	(c) V_g for (a) or (b)	I_a for (c)	Opti- mum Load.	Price.
					ra	m	gm						
P.M.24A	Pentode.. .. .	5-pin	Clear	0.275	—	—	2.0	300	$\left\{ \begin{array}{l} 100 \\ 150 \\ 200 \end{array} \right.$	$\left\{ \begin{array}{l} 9.0 \\ 15.0 \\ 22.5 \end{array} \right.$	$\left\{ \begin{array}{l} 10.0 \\ 15.0 \\ 20.0 \end{array} \right.$	10,000	18/6
P.M.24M	Pentode.. .. .	5-pin	Clear	1.0	—	—	3.0	250	$\left\{ \begin{array}{l} 150 \\ 200 \\ 250 \end{array} \right.$	$\left\{ \begin{array}{l} 9.0 \\ 12.0 \\ 18.0 \end{array} \right.$	$\left\{ \begin{array}{l} 20.0 \\ 30.0 \\ 30.0 \end{array} \right.$	8,000	13/6
P.M.24B	Pentode.. .. .	5-pin	Clear	1.0	—	—	2.1	$\left\{ \begin{array}{l} 250 \\ 300 \\ 400 \end{array} \right.$	$\left\{ \begin{array}{l} 250 \\ 300 \\ 300 \end{array} \right.$	$\left\{ \begin{array}{l} 33.0 \\ 35.0 \\ 40.0 \end{array} \right.$	$\left\{ \begin{array}{l} 25.0 \\ 40.0 \\ 30.0 \end{array} \right.$	8,000	22/6
P.M.24C	Pentode.. .. .	5-pin	Clear	1.0	—	—	3.0	400	200	28.0	30.0	12,000	22/6
P.M.24E	Pentode.. .. .	5-pin	Clear	2.0	—	—	4.0	$\left\{ \begin{array}{l} 250 \\ 500 \end{array} \right.$	$\left\{ \begin{array}{l} 200 \\ 200 \end{array} \right.$	$\left\{ \begin{array}{l} 25.0 \\ 35.0 \end{array} \right.$	$\left\{ \begin{array}{l} 70.0 \\ 50.0 \end{array} \right.$	7,000	45/-
D.O.10	Triode	4-pin	Clear	$\begin{array}{l} 6.0V \\ 0.85A \end{array}$	2,850	2.4	0.85	$\left\{ \begin{array}{l} 200 \\ 300 \\ 400 \end{array} \right.$	$\left\{ \begin{array}{l} — \\ — \\ — \end{array} \right.$	$\left\{ \begin{array}{l} 60.0 \\ 90.0 \\ 130.0 \end{array} \right.$	$\left\{ \begin{array}{l} 17.0 \\ 25.0 \\ 25.0 \end{array} \right.$	6,000	25/-
D.O.20	Triode	4-pin	Clear	$\begin{array}{l} 7.5V \\ 1.1A \end{array}$	2,000	5.0	2.5	$\left\{ \begin{array}{l} 350 \\ 400 \\ 425 \end{array} \right.$	$\left\{ \begin{array}{l} — \\ — \\ — \end{array} \right.$	$\left\{ \begin{array}{l} 52.5 \\ 61.5 \\ 66.0 \end{array} \right.$	$\left\{ \begin{array}{l} 34.0 \\ 38.0 \\ 40.0 \end{array} \right.$	5,000	30/-
D.O.24	Triode	4-pin	Clear	2.0	1,390	9.0	6.5	$\left\{ \begin{array}{l} 200 \\ 300 \\ 400 \end{array} \right.$	$\left\{ \begin{array}{l} — \\ — \\ — \end{array} \right.$	$\left\{ \begin{array}{l} 13.0 \\ 24.0 \\ 34.0 \end{array} \right.$	$\left\{ \begin{array}{l} 40.0 \\ 50.0 \\ 63.0 \end{array} \right.$	4,000	25/-
D.O.25	Triode	4-pin	Clear	$\begin{array}{l} 6.0V \\ 1.1A \end{array}$	800	3.0	3.75	$\left\{ \begin{array}{l} 200 \\ 300 \\ 400 \end{array} \right.$	$\left\{ \begin{array}{l} — \\ — \\ — \end{array} \right.$	$\left\{ \begin{array}{l} 45.0 \\ 78.0 \\ 112.0 \end{array} \right.$	$\left\{ \begin{array}{l} 60.0 \\ 60.0 \\ 63.0 \end{array} \right.$	4,000	30/-
D.O.26	Triode	4-pin	Clear	2.0	600	3.8	6.3	$\left\{ \begin{array}{l} 200 \\ 300 \\ 400 \end{array} \right.$	$\left\{ \begin{array}{l} — \\ — \\ — \end{array} \right.$	$\left\{ \begin{array}{l} 40.0 \\ 63.0 \\ 92.0 \end{array} \right.$	$\left\{ \begin{array}{l} 38.0 \\ 50.0 \\ 63.0 \end{array} \right.$	4,000	25/-