

MULLARD FULL-WAVE RECTIFIERS

| Type. | Description. | Base. | Vf | If | Max. Va (r.m.s.) | Max. Rectified Output (mA). | Price. |
|--------------|--|-------|-----|-----|------------------|-----------------------------|--------|
| D.W.2 .. | Directly-heated F.W. Rectifier | 4-pin | 4.0 | 1.0 | 250-0-250 | 60 | 10/6 |
| D.W.3 .. | Directly-heated F.W. Rectifier | 4-pin | 4.0 | 2.0 | 350-0-350 | 120 | 10/6 |
| D.W.4/350 .. | Directly-heated F.W. Rectifier | 4-pin | 4.0 | 2.0 | 350-0-350 | 120 | 10/6 |
| D.W.4 .. | Directly-heated F.W. Rectifier | 4-pin | 4.0 | 2.0 | 500-0-500 | 120 | 15/- |
| D.W.4/500 .. | Directly-heated F.W. Rectifier | 4-pin | 4.0 | 2.0 | 500-0-500 | 120 | 15/- |
| I.W.2 .. | Indirectly-heated F.W. Rectifier | 4-pin | 4.0 | 1.2 | 250-0-250 | 60 | 10/6 |
| I.W.3 .. | Indirectly-heated F.W. Rectifier | 4-pin | 4.0 | 2.4 | 350-0-350 | 120 | 10/6 |
| IW4/350 .. | Indirectly-heated F.W. Rectifier | 4-pin | 4.0 | 2.0 | 350-0-350 | 120 | 10/6 |
| I.W.4 .. | Indirectly-heated F.W. Rectifier | 4-pin | 4.0 | 2.4 | 500-0-500 | 120 | 15/- |

Page 90

MULLARD D.C. MAINS VALVES (DIRECTLY-HEATED)

| Type. | Description. | Base. | Bulb Finish. | If. | Characteristics at Va = 100; Vg = 0. | | | (a) Va | (b) Vs or Vaux | (c) Vg for (a) or (b) | Ia for (c) | Optimum Load. | Price. |
|---------|----------------------------|-------------------|--------------|-----|--------------------------------------|-----|-----|---------------------|----------------|---------------------------------|---------------------|---------------|--------|
| | | | | | ra | m | gm | | | | | | |
| P.M.13 | Screened Tetrode | { 4-pin 5-pin | Clear Met. } | 0.1 | 360,000 | 250 | 0.7 | 200 | 100 | 0 | 4.0 | — | 20/- |
| P.M.4DX | Medium Impedance Triode .. | 4-pin | Clear | 0.1 | 7,500 | 15 | 2.0 | { 100 125 150 | { — — — | { 1.5-3.0 3.0-4.5 4.5-6.0 | { 1.5 2.0 2.5 | — | 8/6 |
| P.M.25 | Output Pentode | 4-pin or 5-pin | Clear | 0.1 | — | — | 1.6 | 150 | 150 | 15.0 | 10.0 | 8,000 | 17/6 |